NSN 5910-01-171-9405



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-171-9405 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 1.0000 **Terminal Length:** 1.625 inches **Body Diameter:** 0.170 inches **Body Length:** 0.500 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 0.022 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -2.00/+2.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:**

200000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.2000

Case Insulation Material:

Plastic

Test Data Document:

81349-mil-c-39022/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5910-01-171-9405

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0