

View Online at https://aerobasegroup.com/nsn/5910-01-172-1001

2a Body Style: Piston Bushing Diameter: 0.193 inches Bushing Length: 0.350 inches Body Length: 0.719 inches
Piston Bushing Diameter: 0.193 inches Bushing Length: 0.350 inches Body Length:
Bushing Diameter: 0.193 inches Bushing Length: 0.350 inches Body Length:
0.193 inches Bushing Length: 0.350 inches Body Length:
Bushing Length: 0.350 inches Body Length:
0.350 inches Body Length:
Body Length:
0.719 inches
Overall Diameter:
0.312 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Terminal Diameter:
0.093 inches
Terminal Thickness:
0.018 inches
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Terminal Location:
End opposite adjustment control perpendicular
Adjustment Device Torque:
Between 1.000 inch-ounces and 8.000 inch-ounces
Bushing Shape:
Round w/flat
Insulation Dc Resistance At 25 Deg Celsius:
1000000.0 megohms
Bushing Width:
0.173 inches
Mounting Facility Type And Quantity:
1 threaded bushing
Thready Qty Per Inch (tpi):
32
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.190 inches
Capacitance Range In Picofarads:
+1.0/+28.0 single section



Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 hex socket

Terminal Type And Quantity:

1 tab, solder lug and 1 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0