NSN 5910-01-172-2308

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-172-2308

| Body Style: |
|---|
| W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 0.062 inches 0.062 inches |
| Body Diameter: |
| 2.078 inches |
| Body Length: |
| 3.850 inches |
| Terminal Diameter: |
| 0.190 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 21000.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 20.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+75.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Equivalent Series Resistance At Reference Tempurature In Ohms: |
| 0.009 |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 threaded hole |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5910-01-172-2308

Electrolytic Fixed Capacitor - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A010b0