# NSN 5910-01-172-6355

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-172-6355

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

#### **Reliability Indicator:**

Not establishednot established

# **Terminal Length:**

1.500 inches 1.500 inches 1.500 inches

**Body Diameter:** 

0.385 inches

**Body Length:** 

1.625 inches

**Terminal Diameter:** 

0.032 inches

#### **Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Anode Type:** 

Plain foil

#### **Electrical Polarization:**

Polarized

#### **Capacitance Value Per Section:**

350.000 microfarads single section

# **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

#### Dc Leakage At Maximum Operating Temp:

50.0 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

16.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:** 

Metal

## **Capacitive Electrode Material:**

Aluminum

#### **Equivalent Series Resistance At Reference Tempurature In Ohms:**

250.00

#### Dc Leakage At Reference Temp:

9.000 microamperes

#### **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-01-172-6355

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0