NSN 5910-01-172-8503

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-172-8503

Body Style:

W/thd mtg hol (s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

Between 12.650 inches and 12.850 inches

Body Width:

Between 4.820 inches and 4.900 inches

Body Height:

4.750 inches

Center To Center Distance Between Terminals Parallel To Length:

9.500 inches

Terminal Diameter:

0.250 inches

Terminal Height From Body:

Between 0.750 inches and 1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

12.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Internal Electrical Connection Type:

Extended foil

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting studs

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.500 microfarads single section

Nonderated Operating Temp:

Between 0.0 degrees celsius and 80.0 degrees celsius

Thread Size:

0.190 inches

Nonderated Continuous Voltage Rating And Type Per Section:

40000.0 dc single section

Tolerance Range Per Section:

-5.00/+15.00 percent single section

Case Material:

Metal

NSN 5910-01-172-8503

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Insulation Resistance At Reference Temp:
1000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Dielectric Material:
Plastic
Terminal Type And Quantity:
2 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0