NSN 5910-01-174-3554

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-174-3554

Body Style:					
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals					
Reliability Indicator:					
Not establishednot established					
Terminal Length:					
1.500 inches 1.500 inches 1.500 inches					
Body Diameter:					
0.289 inches					
Body Length:					
0.686 inches					
Terminal Diameter:					
0.025 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Anode Type:					
Solid					
Electrical Polarization:					
Polarized					
Capacitance Value Per Section:					
10.000 microfarads single section					
Nonderated Operating Temp:					
Between -80.0 degrees celsius and 85.0 degrees celsius					
Nonderated Continuous Voltage Rating And Type Per Section:					
75.0 dc single section					
Tolerance Range Per Section:					
-10.00/+10.00 percent single section					
Case Material:					
Metal					
Capacitive Electrode Material:					
Tantalum					
Dissipation Factor At Reference Tempurature In Percent:					
6.0000					
Dc Leakage At Reference Temp:					
8.000 microamperes					
Terminal Surface Treatment:					
Solder					
Case Insulation Material:					
Plastic					
Terminal Type And Quantity:					
2 uninsulated wire lead					
Shelf Life:					

N/a

NSN 5910-01-174-3554

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0