NSN 5910-01-175-2410

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-175-2410

Body Style:						
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals						
Reliability Indicator:						
Not establishednot established						
Terminal Length:						
1.500 inches 1.500 inches 1.500 inches						
Body Diameter:						
0.135 inches						
Body Length:						
0.458 inches						
Terminal Diameter:						
0.020 inches						
Schematic Diagram Designator:						
Electrod (s) grounded to case, w/gnd terminal						
Anode Type:						
Solid						
Electrical Polarization:						
Polarized						
Features Provided:						
Hermetically sealed case						
Capacitance Value Per Section:						
0.470 microfarads single section						
Nonderated Operating Temp:						
Between -80.0 degrees celsius and 85.0 degrees celsius						
Nonderated Continuous Voltage Rating And Type Per Section:						
15.0 dc single section						
Tolerance Range Per Section:						
-10.00/+10.00 percent single section						
Case Material:						
Metal						
Capacitive Electrode Material:						
Tantalum						
Dissipation Factor At Reference Tempurature In Percent:						
2.0000						
Dc Leakage At Reference Temp:						
0.500 microamperes						
Terminal Surface Treatment:						
Solder						
Terminal Type And Quantity:						
2 uninsulated wire lead						
Shelf Life:						

N/a

NSN 5910-01-175-2410

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0