## NSN 5910-01-176-4499

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-176-4499

Body Style:						
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals						
Reliability Indicator:						
Not establishednot established						
Terminal Length:						
1.500 inches 1.500 inches 1.500 inches						
Body Diameter:						
0.219 inches						
Body Length:						
0.955 inches						
Terminal Diameter:						
0.020 inches						
Schematic Diagram Designator:						
No common or grounded electrode (s)						
Anode Type:						
Solid						
Electrical Polarization:						
Nonpolarized						
Capacitance Value Per Section:						
30.000 microfarads single section						
Nonderated Operating Temp:						
Between -55.0 degrees celsius and 85.0 degrees celsius						
Nonderated Continuous Voltage Rating And Type Per Section:						
6.0 dc single section						
Tolerance Range Per Section:						
-10.00/+10.00 percent single section						
Case Material:						
Metal						
Capacitive Electrode Material:						
Tantalum						
Dissipation Factor At Reference Tempurature In Percent:						
6.0000						
Dc Leakage At Reference Temp:						
1.000 microamperes						
Terminal Surface Treatment:						
Solder						
Case Insulation Material:						
Plastic						
Terminal Type And Quantity:						
2 uninsulated wire lead						
Shelf Life:						

N/a

## NSN 5910-01-176-4499

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0