## NSN 5910-01-176-5030

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-176-5030

**Body Style:** 

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Body Length:** 

Between 3.130 inches and 3.370 inches

**Body Width:** 

Between 2.020 inches and 2.060 inches

**Body Height:** 

1.070 inches

**Center To Center Distance Between Terminals Parallel To Width:** 

Between 0.850 inches and 1.150 inches

**Terminal Height From Body:** 

0.500 inches

**Unthreaded Mounting Hole Diameter:** 

0.191 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.610 inches and 2.650 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.730 inches and 2.770 inches

**Mounting Facility Type And Quantity:** 

4 unthreaded mounting holes

Capacitance Value Per Section:

3.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

450.0 dc single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

4000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1500

**Terminal Type And Quantity:** 

2 threaded stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-01-176-5030

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0