NSN 5910-01-176-5030

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-176-5030

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

Between 3.130 inches and 3.370 inches

Body Width:

Between 2.020 inches and 2.060 inches

Body Height:

1.070 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.850 inches and 1.150 inches

Terminal Height From Body:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.191 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.610 inches and 2.650 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.730 inches and 2.770 inches

Mounting Facility Type And Quantity:

4 unthreaded mounting holes

Capacitance Value Per Section:

3.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

450.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

4000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.1500

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5910-01-176-5030

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0