NSN 5910-01-176-5551

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-176-5551

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.0010 **Terminal Length:** 1.625 inches **Body Diameter:** 0.342 inches **Body Length:** 1.013 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 300000.0 megohms **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 3000000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.1500 **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

2 uninsulated wire lead

81349-mil-c-83421/1 government specification

Terminal Type And Quantity:

NSN 5910-01-176-5551

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0