## NSN 5910-01-176-6549

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-176-6549

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Diameter:** 

Between 1.938 inches and 2.062 inches

**Body Length:** 

Between 3.438 inches and 3.562 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

Between 0.688 inches and 0.812 inches

**Terminal Diameter:** 

0.190 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**End Application:** 

1270-01-142-2855 target designator set

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

20.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 71.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

2000.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

5000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

1 standoff, threaded stud and 1 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-01-176-6549

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0