Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-176-6549

### **Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.250 inches

### **Body Diameter:**

Between 1.938 inches and 2.062 inches

#### **Body Length:**

Between 3.438 inches and 3.562 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.688 inches and 0.812 inches

**Terminal Diameter:** 

0.190 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

### **End Application:**

1270-01-142-2855 target designator set

### Features Provided:

Hermetically sealed case

### Capacitance Value Per Section:

20.000 microfarads single section

### Nonderated Operating Temp:

Between -40.0 degrees celsius and 71.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

2000.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### Case Material:

Metal

# Insulation Resistance At Reference Temp:

5000.0 megohm-microfarads

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

1 standoff, threaded stud and 1 tab, solder lug

### Shelf Life:

N/a

### Unit Of Measure:

---

Plastic Dielectric Fixed Capacitor - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

A010b0