

View Online at <https://aerobasegroup.com/nsn/5910-01-177-1085>

**Body Style:**

Rotary

**Terminal Length:**

0.080 inches

**Overall Height:**

0.170 inches

**Overall Diameter:**

0.218 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.020 inches

**Dissipation Factor At 25 Deg Celsius In Percent:**

0.5

**Terminal Width:**

0.030 inches

**Terminal Thickness:**

0.008 inches

**End Application:**

5855-01-120-7831 an/aaq-11

**Inclosure Type:**

Encased

**Terminal Location:**

Circumference on end opposite adjustment control bent backward

**Adjustment Device Torque:**

Between 0.300 inch-ounces and 3.000 inch-ounces

**Insulation Dc Resistance At 25 Deg Celsius:**

10000.0 megohms

**Mounting Facility Type And Quantity:**

2 terminal

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Capacitance Range In Picofarads:**

+7.0/+40.0 single section

**Nonderated Voltage Rating And Type:**

25.0 dc continuous single section

**Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:**

+0.00/+14.00 single section and -14.00/-5.00 single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Special Features:**

One dummy terminal

**Test Data Document:**

81349-mil-c-81 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 printed circuit

**Specification Data:**

81349-mil-c-81/6 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A096a0