

View Online at <https://aerobasegroup.com/nsn/5910-01-177-1085>

Body Style:

Rotary

Terminal Length:

0.080 inches

Overall Height:

0.170 inches

Overall Diameter:

0.218 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.020 inches

Dissipation Factor At 25 Deg Celsius In Percent:

0.5

Terminal Width:

0.030 inches

Terminal Thickness:

0.008 inches

End Application:

5855-01-120-7831 an/aaq-11

Inclosure Type:

Encased

Terminal Location:

Circumference on end opposite adjustment control bent backward

Adjustment Device Torque:

Between 0.300 inch-ounces and 3.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+7.0/+40.0 single section

Nonderated Voltage Rating And Type:

25.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

+0.00/+14.00 single section and -14.00/-5.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Special Features:

One dummy terminal

Test Data Document:

81349-mil-c-81 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 printed circuit

Specification Data:

81349-mil-c-81/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0