## NSN 5910-01-177-9061

**Body Style:** 

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-177-9061

| Chip type with tape terminalschip type with tape terminalschip type with tape terminals |
|---|
| Reliability Indicator:  |
| Not establishednot established  |
| Terminal Length:  |
| 0.090 inches 0.090 inches 0.090 inches  |
| Body Length:  |
| 0.320 inches  |
| Body Width:   |
| 0.180 inches  |
| Body Height:  |
| 0.195 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Anode Type:   |
| Solid   |
| Impedance At Minimum Operating Tempurature In Ohms:                                     |
| 0.25  |
| Electrical Polarization:  |
| Polarized   |
| Capacitance Value Per Section:  |
| 15.000 microfarads single section   |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 85.0 degrees celsius                                  |
| Dc Leakage At Maximum Operating Temp:   |
| 30.0 microamperes   |
| Nonderated Continuous Voltage Rating And Type Per Section:                              |
| 20.0 dc single section  |
| Criticality Code Justification:   |
| Feat  |
| Tolerance Range Per Section:  |
| -10.00/+10.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Tantalum  |

4.000

Dc Leakage At Reference Temp:

**Dissipation Factor At Reference Tempurature In Percent:** 

2.000 microamperes

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-177-9061

Electrolytic Fixed Capacitor - Page 2 of 2



| Special Features:           |
|-----------------------------|
| Burn-in test                |
| Terminal Type And Quantity: |
| 2 bonding pad               |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |
| Fiig:                       |

A010b0