NSN 5910-01-177-9063

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-177-9063 **Body Style:** Chip typechip typechip type **Reliability Indicator:** Not establishednot established **Terminal Length:** 0.040 inches 0.040 inches 0.040 inches **Body Length:** 0.320 inches **Body Width:** 0.180 inches **Body Height:** 0.195 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 0.23 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 4.700 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 45.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Criticality Code Justification:** Feat **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 4.0000 Dc Leakage At Reference Temp: 3.000 microamperes **Terminal Surface Treatment:**

Solder

NSN 5910-01-177-9063

Electrolytic Fixed Capacitor - Page 2 of 2



Special Features:
Burn-in test
Terminal Type And Quantity:
2 bonding pad
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0