## NSN 5910-01-178-9574

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-178-9574 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.1000 **Terminal Length:** 1.250 inches **Body Length:** 0.190 inches **Body Width:** 0.190 inches **Body Height:** 0.090 inches Center To Center Distance Between Terminals Parallel To Length: 0.200 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 270.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Test Data Document:** 81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5910-01-178-9574

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0