## NSN 5910-01-179-4762

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-179-4762

Body	Style:
------	--------

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.187 inches 0.187 inches

**Body Diameter:** 

0.350 inches

**Body Length:** 

0.650 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.250 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Solid

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

100.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

4.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

Case Material:

Plastic

**Capacitive Electrode Material:** 

Tantalun

**Dissipation Factor At Reference Tempurature In Percent:** 

10.0000

Dc Leakage At Reference Temp:

10.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-179-4762

Electrolytic Fixed Capacitor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A010b0