NSN 5910-01-180-8229

Thread Class:

Body Style:

2a

Piston

Glass Dielectric Variable Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-01-180-8229



Terminal Length:
1.500 inches
Bushing Diameter:
Between 0.251 inches and 0.255 inches
Bushing Length:
0.250 inches
Body Length:
0.484 inches
Overall Diameter:
0.250 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Terminal Diameter:
0.025 inches
Quality Factor At 25 Deg Celsius:
1000.0
Mounting Facility Screw Thread Series Designator:
Unef
Inclosure Type:
Encapsulated
Adjustment Device Torque:
Between 1.000 inch-ounces and 10.000 inch-ounces
Bushing Shape:
Round w/flat
Insulation Dc Resistance At 25 Deg Celsius:
1000000.0 megohms
Bushing Width:
Between 0.230 inches and 0.234 inches
Mounting Facility Type And Quantity:
1 threaded bushing
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.250 inches
Capacitance Range In Picofarads:
+0.8/+5.0 single section
Nonderated Voltage Rating And Type:

750.0 dc continuous single section

NSN 5910-01-180-8229

Glass Dielectric Variable Capacitor - Page 2 of 2



Fiig: A096a0