

NSN 5910-01-181-6650 Ceramic Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-181-6650 **Body Style:** Rotary **Terminal Length:** 0.118 inches **Body Length:** 0.268 inches **Body Width:** 0.256 inches **Body Height:** 0.197 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -200.0/+200.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.206 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.206 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Terminal Width:** 0.039 inches **Terminal Thickness:**

0.010 inches

Inclosure Type:

Encased

Adjustment Device Torque:

Between 0.280 inch-ounces and 2.800 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

100000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+2.5/+9.0 single section

Nonderated Voltage Rating And Type:

100.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

2 printed circuit

NSN 5910-01-181-6650

Ceramic Dielectric Variable Capacitor - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0