NSN 5910-01-182-0140

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-182-0140

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot established

Terminal Length:

Between 2.500 inches and 2.500 inches and 2.500 inches and 3.500 inches 3.500 inches

Body Diameter:

0.645 inches

Body Length:

2.656 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

2.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

680.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 microfarads single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.41

Dc Leakage At Reference Temp:

0.500 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-182-0140

Electrolytic Fixed Capacitor - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_1	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0