NSN 5910-01-182-0620

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-182-0620 **Body Style:** W/mtg bracket, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 0.296 inches **Body Diameter:** 1.000 inches **Body Length:** 1.875 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Type And Quantity:** 1 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 600.0 megohms **Capacitance Value Per Section:** 1.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 1300.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life:

N/a **Unit Of Measure:**

NSN 5910-01-182-0620

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ | | | ٠. | | | | | | | | |
|---|---|---|----|----|-----|----|---|----|---|---|--|
| n | Δ | m | ш | 11 | o r | 17 | 9 | H | ^ | n | |
| _ | ㄷ | | • | IL | aı. | 14 | а | LI | u | | |

No

Fiig:

A010b0