Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-182-0736

Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Establishedestablished

Reliability Failure Rate Level In Percent:

1.00001.00001.0000

Terminal Length:

2.500 inches 2.500 inches 2.500 inches

Body Diameter:

1.035 inches

Body Length:

Between 3.625 inches and 3.843 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.300 inches

Terminal Diameter:

Between 0.038 inches and 0.048 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Impedance At Minimum Operating Tempurature In Ohms:

0.122

Electrical Polarization:

Polarized

Capacitance Value Per Section:

320.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

760.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.405

Dc Leakage At Reference Temp:

126.000 microamperes

Terminal Surface Treatment:

Solder

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:

Plastic

Test Data Document:

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 uninsulated wire lead

Specification Data:

81349-mil-c-39018/7 government specification

Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0