

View Online at https://aerobasegroup.com/nsn/5910-01-182-8362

| view Online at https://aerobasegroup.com/hsn/3910-01-102-0302 | |
|---|--|
| Body Style: | |
| Chip type | |
| Reliability Indicator: | |
| Not established | |
| Terminal Length: | |
| Between 0.010 inches and 0.035 inches | |
| Body Length: | |
| Between 0.085 inches and 0.105 inches | |
| Body Width: | |
| Between 0.040 inches and 0.065 inches | |
| Body Height: | |
| 0.065 inches | |
| Schematic Diagram Designator: | |
| No common or grounded electrode (s) | |
| End Application: | |
| Radio set an/prc-113 | |
| Insulation Resistance At Maximum Operating Temp: | |
| 10000.0 megohms | |
| Capacitance Value Per Section: | |
| 0.010 microfarads single section | |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: | |
| -15.0/+15.0 without voltage applied single section | |
| Nonderated Operating Temp: | |
| Between -55.0 degrees celsius and 125.0 degrees celsius | |
| Nonderated Continuous Voltage Rating And Type Per Section: | |
| 50.0 dc single section | |
| Tolerance Range Per Section: | |
| -10.00/+10.00 percent single section | |
| Case Material: | |
| Ceramic | |
| Insulation Resistance At Reference Temp: | |
| 100000.0 megohms | |
| Dissipation Factor At Reference Tempurature In Percent: | |
| 2.5000 | |
| Terminal Surface Treatment: | |
| Solder | |
| Terminal Type And Quantity: | |
| 2 bonding pad | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |



Demilitarization:

No

Fiig:

A010b0