## NSN 5910-01-183-3107

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-183-3107

Body	Stv	-ما
DUUV	OLV.	ıc.

W/twist tab mtg, terminal (s) on one endw/twist tab mtg, terminal(s) on one endw/twist tab mtg, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.328 inches 0.328 inches 0.328 inches

**Body Diameter:** 

Between 1.359 inches and 1.421 inches

**Body Length:** 

Between 3.438 inches and 3.562 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case

**Anode Type:** 

Etched foil

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

200.000 microfarads single section

**Nonderated Operating Temp:** 

Between -30.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

18.000

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

1.40

Dc Leakage At Reference Temp:

1.500 milliamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

1 tab, solder lug

Shelf Life:

N/a

## NSN 5910-01-183-3107

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A010b0