

View Online at https://aerobasegroup.com/nsn/5910-01-183-6479

| Body Style:   |
|---|
| Rotary  |
| Terminal Length:  |
| 0.110 inches  |
| Body Diameter:  |
| 0.350 inches  |
| Body Height:  |
| 0.315 inches  |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:              |
| -450.0 single section   |
| Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:                |
| -250.0/+250.0 single section  |
| Center To Center Distance Between Terminals Parallel To Diameter:           |
| 0.295 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Diameter: |
| 0.295 inches  |
| Quality Factor At 25 Deg Celsius:   |
| 500.0   |
| Terminal Width:   |
| 0.040 inches  |
| Terminal Thickness:   |
| 0.015 inches  |
| Inclosure Type:   |
| Encased   |
| Terminal Location:  |
| Circumference perpendicular   |
| Adjustment Device Torque:   |
| Between 0.300 inch-ounces and 3.000 inch-ounces                             |
| Insulation Dc Resistance At 25 Deg Celsius:                                 |
| 10000.0 megohms   |
| Mounting Facility Type And Quantity:  |
| 3 terminal  |
| Nonderated Operating Temp:  |
| Between -20.0 degrees celsius and 85.0 degrees celsius                      |
| Capacitance Range In Picofarads:  |
| +2.3/+20.0 single section   |
| Nonderated Voltage Rating And Type:   |
| 250.0 dc continuous single section  |
| Adjustment Device Drive Type And Quantity:                                  |
| 1 slotted screw   |
| Terminal Type And Quantity:   |
| 3 printed circuit   |



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A096a0