Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-184-0628

### Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

Terminal Length:

1.100 inches

Body Length:

0.550 inches

**Body Width:** 

0.320 inches

**Body Height:** 

0.170 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.382 inches and 0.422 inches

#### **Terminal Diameter:**

Between 0.022 inches and 0.026 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

### **End Application:**

6625-00-463-6042 recorder, test set

### Capacitance Value Per Section:

0.0022 microfarads single section

### Nonderated Operating Temp:

Between -40.00 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

250.0 ac-rms single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

1000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.5000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

--



Demilitarization:

No

Fiig:

A010b0