

View Online at <https://aerobasegroup.com/nsn/5910-01-184-5232>

**Body Style:**

Pellet type, w/thd mtg hole/studpellet type, w/thd mtg hole/studpellet type, w/thd mtg hole/stud

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

0.312 inches 0.312 inches 0.312 inches

**Body Diameter:**

0.853 inches

**Body Length:**

0.320 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case

**Anode Type:**

Solid

**Impedance At Minimum Operating Tempurature In Ohms:**

35.0

**Electrical Polarization:**

Polarized

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

1 threaded mounting studs

**Capacitance Value Per Section:**

220.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.164 inches

**Dc Leakage At Maximum Operating Temp:**

24.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Tempurature In Percent:**

33.6000

**Dc Leakage At Reference Temp:**

3.000 microamperes

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-83500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

1 pin

**Specification Data:**

81349-mil-c-83500/1a government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0