## NSN 5910-01-184-9266



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-184-9266 **Body Style:** W/o mtg facilities, axial terminals **Dummy Terminal Quantity: Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.0100 **Terminal Length:** 1.500 inches **Body Diameter:** 1.010 inches **Body Length:** 2.750 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Impedance At Minimum Operating Tempurature In Ohms:** 0.4 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 330.000 microfarads single section **Nonderated Operating Temp:** Between 55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+100.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 64.000 microamperes **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 3 insulated wire lead

Shelf Life:

N/a

## NSN 5910-01-184-9266

Electrolytic Fixed Capacitor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A010b0