NSN 5910-01-186-0099

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-186-0099

| · · |
|--|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| 0.570 inches |
| Body Width: |
| 0.170 inches |
| Body Height: |
| 0.290 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 1000.0 megohms |
| Capacitance Value Per Section: |
| 0.022 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 105.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.3000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5910-01-186-0099

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0