Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-186-4572

## Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.236 inches

**Body Length:** 

0.512 inches

#### **Body Width:**

0.354 inches

**Body Height:** 

#### 0.157 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.394 inches

**Terminal Diameter:** 

0.031 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.068 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

400.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

#### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-200.0/+200.0 single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

30000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## Shelf Life:

N/a



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0