## NSN 5910-01-186-5406

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-186-5406

<b>D</b> -	٠. د	C4	٠
DU	uv	Stv	ıe:

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.063 inches 0.063 inches 0.063 inches

**Body Diameter:** 

2.078 inches

**Body Length:** 

4.750 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.875 inches

**Terminal Diameter:** 

0.190 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**End Application:** 

5815-01-069-1766 teletypewriter

**Capacitance Value Per Section:** 

14000.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

15000.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

40.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.05

Dc Leakage At Reference Temp:

6000.000 microamperes

**Case Insulation Material:** 

Plastic

## NSN 5910-01-186-5406

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal	Type And	Quantity:
2 threaded	d hole	

\_ .... ...

Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0