

View Online at <https://aerobasegroup.com/nsn/5910-01-186-6316>

Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

0.875 inches 0.875 inches 0.875 inches

Body Diameter:

0.200 inches

Body Length:

0.540 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

4.700 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.0000

Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0