NSN 5910-01-186-6325

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-186-6325 |
|--|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.236 inches |
| Body Length: |
| 0.512 inches |
| Body Width: |
| 0.354 inches |
| Body Height: |
| 0.157 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.394 inches |
| Terminal Diameter: |
| 0.031 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 1500.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 400.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 1000.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -200.0/+200.0 single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 30000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.0000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |

N/a

NSN 5910-01-186-6325

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A010b0