## NSN 5910-01-186-6326

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-186-6326
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.236 inches
Body Length:
0.512 inches
Body Width:
0.354 inches
Body Height:
0.157 inches
Center To Center Distance Between Terminals Parallel To Length:
0.394 inches
Terminal Diameter:
0.031 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2200.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
400.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
1000.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-200.0/+200.0 single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
30000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead

N/a

Shelf Life:

## NSN 5910-01-186-6326

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0