

View Online at <https://aerobasegroup.com/nsn/5910-01-187-7963>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

5.8 millimeters 5.8 millimeters 5.8 millimeters

**Body Diameter:**

26.4 millimeters

**Body Length:**

53.0 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Electrical Polarization:**

Polarized

**End Application:**

General purpose electronic test equipment, calibration standards equipment, 2m/ate microminature automatic test equipment, wasp class lhd, ticonderoga class c (47) , emory s.Land class as, support equipment b-52 aircraft, oliver perry class ffg, forrestal class cv

**Capacitance Value Per Section:**

10000.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+30.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

0.3500

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.039

**Case Insulation Material:**

Plastic

**Special Features:**

Weapons system essential

**Terminal Type And Quantity:**

1 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0