

View Online at <https://aerobasegroup.com/nsn/5910-01-187-7963>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Terminal Length:

5.8 millimeters 5.8 millimeters 5.8 millimeters

Body Diameter:

26.4 millimeters

Body Length:

53.0 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

End Application:

General purpose electronic test equipment, calibration standards equipment, 2m/ate microminature automatic test equipment, wasp class lhd, ticonderoga class c (47) , emory s.Land class as, support equipment b-52 aircraft, oliver perry class ffg, forrestal class cv

Capacitance Value Per Section:

10000.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+30.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Temperature In Percent:

0.3500

Equivalent Series Resistance At Reference Temperature In Ohms:

0.039

Case Insulation Material:

Plastic

Special Features:

Weapons system essential

Terminal Type And Quantity:

1 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0