## NSN 5910-01-187-7963

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-187-7963

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

## **Reliability Indicator:**

Not establishednot established

## **Terminal Length:**

5.8 millimeters 5.8 millimeters 5.8 millimeters

**Body Diameter:** 

26.4 millimeters

**Body Length:** 

53.0 millimeters

## **Schematic Diagram Designator:**

No common or grounded electrode (s)

#### **Electrical Polarization:**

Polarized

#### **End Application:**

General purpose electronic test equipment, calibration standards equipment, 2m/ate microminiture automatic test equipment, wasp class Ihd, ticonderoga class c (47), emory s.Land class as, support equipment b-52 aircraft, oliver perry class ffg, forrestal class cv

## **Capacitance Value Per Section:**

10000.000 microfarads single section

## **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

## **Criticality Code Justification:**

Feat

## **Tolerance Range Per Section:**

-10.00/+30.00 percent single section

**Case Material:** 

Metal

#### **Capacitive Electrode Material:**

Aluminum

## **Dissipation Factor At Reference Tempurature In Percent:**

0.3500

## **Equivalent Series Resistance At Reference Tempurature In Ohms:**

0.039

#### **Case Insulation Material:**

Plastic

## **Special Features:**

Weapons system essential

## **Terminal Type And Quantity:**

1 printed circuit

## Shelf Life:

N/a

# NSN 5910-01-187-7963

Electrolytic Fixed Capacitor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A010b0