NSN 5910-01-188-5793

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-188-5793

| De de Otales |
|--|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 1.0000 |
| Terminal Length: |
| 1.000 inches |
| Body Length: |
| Between 1.873 inches and 1.918 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.910 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 50.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.3000 |
| Test Data Document: |
| 81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

No

Demilitarization:

NSN 5910-01-188-5793

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0