## NSN 5910-01-188-6283

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-188-6283

D	_	٦,		0	٠			
D	u	u	v	J	ιν	ш	e:	

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.375 inches 0.375 inches

**Body Diameter:** 

0.515 inches

**Body Length:** 

1.740 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.200 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

0.05

**Electrical Polarization:** 

Polarized

**End Application:** 

4920-01-154-8792 collection unit

**Capacitance Value Per Section:** 

640.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.125

Dc Leakage At Reference Temp:

19.000 microamperes

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-188-6283

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0