# NSN 5910-01-188-6856

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-188-6856

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

#### **Reliability Indicator:**

Not establishednot established

## **Terminal Length:**

1.380 inches 1.380 inches 1.380 inches

**Body Diameter:** 

0.866 inches

**Body Length:** 

2.050 inches

**Terminal Diameter:** 

0.031 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

#### **Anode Type:**

Plain foil

## **Impedance At Minimum Operating Tempurature In Ohms:**

4.0

#### **Electrical Polarization:**

Polarized

# **Capacitance Value Per Section:**

10000.000 microfarads single section

#### **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

16.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:** 

Metal

# **Capacitive Electrode Material:**

Aluminum

## **Dissipation Factor At Reference Tempurature In Percent:**

30.0000

## Dc Leakage At Reference Temp:

3.000 microamperes

#### **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-01-188-6856

Electrolytic Fixed Capacitor - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0