## NSN 5910-01-188-9002

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-188-9002

| Body Style:   |
|---|
| W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end |
| Reliability Indicator:  |
| Not establishednot established  |
| Terminal Length:  |
| 0.188 inches 0.188 inches 0.188 inches  |
| Body Diameter:  |
| 0.375 inches  |
| Body Length:  |
| 0.750 inches  |
| Center To Center Distance Between Terminals Parallel To Diameter:   |
| 0.200 inches  |
| Terminal Diameter:  |
| 0.025 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Anode Type:   |
| Plain foil  |
| Electrical Polarization:  |
| Polarized   |
| Capacitance Value Per Section:  |
| 50.000 microfarads single section   |
| Nonderated Operating Temp:  |
| Between -20.0 degrees celsius and 65.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 25.0 dc single section  |
| Tolerance Range Per Section:  |
| -10.00/+100.00 percent single section   |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Aluminum  |
| Dissipation Factor At Reference Tempurature In Percent:   |
| 2.0000  |
| Dc Leakage At Reference Temp:   |
| 3.000 microamperes  |
| Terminal Surface Treatment:   |

Shelf Life: N/a

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Solder

## NSN 5910-01-188-9002

Electrolytic Fixed Capacitor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0