NSN 5910-01-189-3020

Body Style:

Burn-in test

Reliability Indicator:

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-189-3020

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

| Not establishednot established |
|--|
| Terminal Length: |
| 2.500 inches 2.500 inches 2.500 inches |
| Body Diameter: |
| 0.640 inches |
| Body Length: |
| 1.640 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 250.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 95.0 degrees celsius |
| New departs of Continuous Voltage Betting And Torre Ban Continue |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| |
| 50.0 dc single section |
| 50.0 dc single section Criticality Code Justification: |
| 50.0 dc single section Criticality Code Justification: Feat |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum Equivalent Series Resistance At Reference Tempurature In Ohms: |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum Equivalent Series Resistance At Reference Tempurature In Ohms: 0.378 |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum Equivalent Series Resistance At Reference Tempurature In Ohms: 0.378 Dc Leakage At Reference Temp: |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum Equivalent Series Resistance At Reference Tempurature In Ohms: 0.378 Dc Leakage At Reference Temp: 0.224 milliamperes |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum Equivalent Series Resistance At Reference Tempurature In Ohms: 0.378 Dc Leakage At Reference Temp: 0.224 milliamperes Terminal Surface Treatment: |
| 50.0 dc single section Criticality Code Justification: Feat Tolerance Range Per Section: -10.00/+75.00 percent single section Case Material: Metal Capacitive Electrode Material: Aluminum Equivalent Series Resistance At Reference Tempurature In Ohms: 0.378 Dc Leakage At Reference Temp: 0.224 milliamperes Terminal Surface Treatment: Solder |

NSN 5910-01-189-3020

Electrolytic Fixed Capacitor - Page 2 of 2



| Terminal Type Ar | nd Quantity: |
|------------------|--------------|
|------------------|--------------|

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0