

View Online at <https://aerobasegroup.com/nsn/5910-01-189-3120>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Terminal Length:

0.750 inches 0.750 inches 0.750 inches

Body Diameter:

0.175 inches

Body Length:

0.375 inches

Center To Center Distance Between Terminals Parallel To Length:

0.125 inches

Terminal Diameter:

0.020 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

120.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

200.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

10.0000

Dc Leakage At Reference Temp:

20.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0