

View Online at <https://aerobasegroup.com/nsn/5910-01-189-9126>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Terminal Length:

Between 0.167 inches and 0.167 inches and 0.167 inches and 0.207 inches 0.207 inches 0.207 inches

Body Diameter:

0.175 inches

Body Length:

0.350 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.235 inches and 0.265 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

4.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0