## NSN 5910-01-190-0261

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



Body Style: Chip type Reliability Indicator: Not established Body Length: 0.110 inches Body Width: 0.110 inches Body Height: 0.110 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 82.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	View Online at https://aerobasegroup.com/nsn/5910-01-190-0261
Reliability Indicator: Not established Body Length: 0.110 inches Body Width: 0.110 inches Body Height: 0.100 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 82.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Style:
Not established  Body Length: 0.110 inches  Body Width: 0.110 inches  Body Height: 0.100 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 82.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fig:	Chip type
Body Length: 0.110 inches Body Width: 0.110 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 82.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
0.110 inches  Body Width: 0.110 inches  Body Height: 0.100 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 82.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Width: 0.110 inches Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 82.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
0.110 inches  Body Height: 0.100 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 82.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	0.110 inches
Body Height: 0.100 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 82.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Width:
0.100 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  82.000 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Case Material:  Ceramic  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.110 inches
Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 82.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Height:
No common or grounded electrode (s)  Capacitance Value Per Section: 82.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.100 inches
Capacitance Value Per Section: 82.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Schematic Diagram Designator:
82.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	No common or grounded electrode (s)
Nonderated Operating Temp:  Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Case Material:  Ceramic  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Capacitance Value Per Section:
Between -55.0 degrees celsius and 175.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Case Material:  Ceramic  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	82.000 picofarads single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Case Material:  Ceramic  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Nonderated Operating Temp:
90.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Case Material:  Ceramic  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between -55.0 degrees celsius and 175.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	90.0 single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Nonderated Continuous Voltage Rating And Type Per Section:
-30.0/+30.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	100.0 dc single section
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-5.00/+5.00 percent single section  Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	-30.0/+30.0 single section
Case Material: Ceramic  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tolerance Range Per Section:
Ceramic  Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	-5.00/+5.00 percent single section
Terminal Type And Quantity:  2 bonding pad  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Case Material:
2 bonding pad  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ceramic
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 bonding pad
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A010b0	Fiig:
A01000	A010b0