NSN 5910-01-190-1283

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-190-1283

| g |
|---|
| Body Style: |
| W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 15.9 millimeters 15.9 millimeters |
| Body Diameter: |
| 23.0 millimeters |
| Body Length: |
| 43.0 millimeters |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| End Application: |
| 4920-01-111-2981 automatic test |
| Capacitance Value Per Section: |
| 2200.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+30.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.2500 |
| Dc Leakage At Reference Temp: |
| 2.200 microamperes |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 printed circuit |

N/a

Shelf Life:

NSN 5910-01-190-1283

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0