## NSN 5910-01-190-1285

**Body Style:** 

2 uninsulated wire lead

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-190-1285

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:
Not establishednot established
Terminal Length:
0.375 inches 0.375 inches
Body Diameter:
0.413 inches
Body Length:
0.927 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.200 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Impedance At Minimum Operating Tempurature In Ohms:
0.35
Electrical Polarization:
Polarized
End Application:
4920-01-111-2981 automatic test
Capacitance Value Per Section:
100.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 105.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
20.0 dc single section
Tolerance Range Per Section:
-10.00/+100.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:
1.30
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:

## NSN 5910-01-190-1285

Electrolytic Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0