NSN 5910-01-190-1290

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-190-1290

Body Style:					
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end					
Reliability Indicator:					
Not establishednot established					
Terminal Length:					
0.984 inches 0.984 inches 0.984 inches					
Body Diameter:					
0.197 inches					
Body Length:					
0.433 inches					
Center To Center Distance Between Terminals Parallel To Diameter:					
0.078 inches					
Terminal Diameter:					
0.019 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Anode Type:					
Plain foil					
Impedance At Minimum Operating Tempurature In Ohms:					
2.0					
Electrical Polarization:					
Polarized					
Capacitance Value Per Section:					
4.700 microfarads single section					
Nonderated Operating Temp:					
Between -40.0 degrees celsius and 85.0 degrees celsius					
Nonderated Continuous Voltage Rating And Type Per Section:					
50.0 dc single section					
Tolerance Range Per Section:					
-20.00/+20.00 percent single section					
Case Material:					
Metal					
Capacitive Electrode Material:					
Aluminum					
Dissipation Factor At Reference Tempurature In Percent:					
10.0000					
Dc Leakage At Reference Temp:					

Solder

Case Insulation Material:

Terminal Surface Treatment:

4.000 microamperes

Plastic

NSN 5910-01-190-1290

Electrolytic Fixed Capacitor - Page 2 of 2



Ī	erminal	Type	And	Quant	tity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0